

Features:

- 350 Watt / 3 Output Power Supply
- Hot-Swap Package Package of **8.77 x 3.82 x 1.58"**
- **80% Efficiency** (typical)
- Internal OR'ng Diodes with Active Current Sharing
- 5VSB @ 2.0A Auxiliary Output
- Sequenced Output Turn-On
- Full-Featured Status & Control Functions
- International Safety Approvals
- 3 Year Warranty

Input Specifications:

- Universal AC Input (90-264VAC / 47~63Hz)
- Active Power Factor Correction
- Less than 300µA Leakage Current
- 80% Operational Efficiencies

Output Specifications:

- No Minimum Load
- 5VSB @ 2.0A Auxiliar Output
- Less than 300µA Leakage Current
- 1+1 Redundant Operation with Internal OR'ng Diodes
- Ripple less than ±1% pk-pk maximum
- Over-Current / Over-Voltage / Over-Temp Protection

Environmental Specifications:

- 0~50°C Operation (internal Ball Bearing Fans)
- -40~+85°C Storage Temperature
- 5~95% Humidity (non-condensing)
- >200k Hours MTBF per MIL-HDBK 217F

Safety / Emissions:

- EN55011 / EN55022 Level B Emissions
- UL/cUL 60950-1 Safety Approval
- CB Report (EN60950-1)
- CE Mark (LVD)

Model	V1 ⁽¹⁾	V2 ⁽¹⁾	V3
ARM-3513-00	3.3V 28A	5V 30A	12V 15A

Total output power not to exceed 350W continuous

(1) combined power not to exceed 200W continuous

