



92x92x25 mm

Model	P/N	Bearing	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-HzO)	(dBA)	(g)
KD1209PTB1	13.(2).GN	●	12	160	1.9	2800	49.0	0.17	35.0	95
KD1209PTB2	13.(2).GN	●	12	130	1.6	2600	48.0	0.15	33.0	95
KD1209PTB3	13.(2).GN	●	12	90	1.1	2300	41.0	0.11	30.0	95
KD1209PTS1	13.GN	●	12	160	1.9	2800	49.0	0.16	34.0	95
KD1209PTS2	13.GN	●	12	130	1.6	2500	44.5	0.14	32.0	95
KD1209PTS3	13.GN	●	12	100	1.2	2200	39.0	0.11	28.0	95
KD2409PTB1	13.(2).A.GN	●	24	75	1.8	2800	49.0	0.17	35.0	100
KD2409PTB2	13.(2).A.GN	●	24	60	1.4	2600	48.0	0.15	33.0	100
KD2409PTB3	13.(2).A.GN	●	24	43	1.0	2300	41.0	0.11	30.0	100
KD2409PTS1	13.A.GN	●	24	76	1.8	2800	49.0	0.16	34.0	100
KD2409PTS2	13.A.GN	●	24	61	1.5	2500	44.5	0.14	32.0	100
KD2409PTS3	13.A.GN	●	24	49	1.2	2200	39.0	0.11	28.0	100

