



Model	P/N	Bearing	Rating Voltage (VDC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H <sub>2</sub> O)	Noise (dBA)	Weight (g)
KDE1212PMV1	13.MS.A.GN	● VAPO ⊕ 2BALL	12	0.853	10.2	3000	145	0.32	50	300
KDE1212PMV2	13.MS.A.GN	●	12	0.655	7.9	2700	128	0.25	46	300
KDE1212PMV3	13.MS.A.GN	●	12	0.481	5.8	2400	113	0.20	43	300
KDE2412PMV1	13.MS.A.GN	●	24	0.413	9.9	3000	145	0.32	50	300
KDE2412PMV2	13.MS.A.GN	●	24	0.312	7.5	2700	128	0.25	46	300
KDE2412PMV3	13.MS.A.GN	●	24	0.239	5.7	2400	113	0.20	43	300
KDE4812PMV1	13.MS.A.GN	●	48	0.225	10.8	3000	145	0.32	50	300
KDE4812PMV2	13.MS.A.GN	●	48	0.168	8.1	2700	128	0.25	46	300
KDE4812PMV3	13.MS.A.GN	●	48	0.128	6.1	2400	113	0.20	43	300

Model	P/N	Bearing	Rating Voltage (VDC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H <sub>2</sub> O)	Noise (dBA)	Weight (g)
PMD1212PMB1-A	(2).GN	⊕	12	1.6	19.2	4200	190	0.65	54	330
PMD1212PMB2-A	(2).GN	⊕	12	1.2	14.4	3800	170	0.54	51	330
PMD1212PMB3-A	(2).GN	⊕	12	0.83	10.0	3400	153	0.43	48	330
PMD2412PMB1-A	(2).GN	⊕	24	0.76	18.2	4200	190	0.65	54	330
PMD2412PMB2-A	(2).GN	⊕	24	0.57	13.7	3800	170	0.54	51	330
PMD2412PMB3-A	(2).GN	⊕	24	0.42	10.1	3400	153	0.43	48	330
PMD4812PMB1-A	(2).GN	⊕	48	0.4	19.2	4200	190	0.65	54	330
PMD4812PMB2-A	(2).GN	⊕	48	0.3	14.4	3800	170	0.54	51	330
PMD4812PMB3-A	(2).GN	⊕	48	0.22	10.6	3400	153	0.43	48	330

